

GLASS

SOLUTIONS

GRINDING

EDGING MACHINES
BEVELLING MACHINES

WASHING

VERTICAL WASHING MACHINES

COMPLEMENTARY PROCESSING



CORNERS GRINDING MACHINES
HORIZONTAL DRILLING MACHINES



LATTUADA
+ ADDING VALUE



adeliolattuada.com



GLASS

SOLUTIONS

GRINDING SOLUTIONS 8

STRAIGHT-LINE **EDGING MACHINES** 10

ALM SERIES		12
TL SERIES		16
TLR SERIES		20
TLS SERIES		26

STRAIGHT-LINE **BEVELLING MACHINES** 32

GAMMA SERIES		34
--------------	---	----

WASHING SOLUTIONS 38

VERTICAL WASHING MACHINES 40

OT SERIES		42
CT SERIES		46
CTS SERIES		50

COMPLEMENTARY PROCESSING 54

PROCESSING MACHINES

COMPLEMENTARY 56

DELTA SERIES		58
TP SERIES		62

ADDING
VALUE



THE INESTIMABLE VALUE OF GIVING AND RECEIVING

THE VALUE RECEIVED

Every person who has trusted Lattuada has enriched its story. Each glass (or stone) processing solution completed and put into production has added even more experience and drive.

THE VALUE OFFERED

Building on many years of market knowledge and a vast portfolio of successful projects, Lattuada continues to invest in development, research and training. With continually updated internal and external feedback, it strives to offer more quality, more solutions, more technology.

ADDING + VALUE

A SYNERGY OF VALUES CALLED COMPANY

Quality and personalisation

Are the hallmark of Lattuada's design. Attention to every detail is pursued within a customised production process, with care and attention.

Flexibility and assistance

Maximum willingness to listen and develop the client's requests. Guarantee of follow-up and further customisation throughout the machine life cycle.

History and experience

Since 1978, day after day, milestone after milestone, Lattuada has continued to grow in its problem-solving capacity and in guaranteeing progressive know-how to all its customers.

Internationality and Italianity

Made in Italy represents worldwide excellence in the glass sector. The sense of belonging coexists with the pride of constantly interacting with an international audience.

Innovation and substance

Proposing new solutions is part of Lattuada's DNA. Simplification, training and constant support are the pluses offered to combine technology and user-friendliness.

Eco-Sustainability and territory

Starting from the Italian headquarters, concrete actions for the environment have been undertaken for years. Likewise, Lattuada's solutions will be increasingly "green".

AS BIG AS THE WORLD.

OUR SOLUTIONS ARE WORKING ALL OVER THE WORLD. SINCE 2017 WE OPERATE IN THE USA THROUGH LATTUADA NORTH AMERICA BASED IN NORTHWOOD (OHIO). A PRECISE CORPORATE CHOICE TO STAY CLOSE TO OUR CUSTOMERS BY OFFERING TOP QUALITY SERVICES AND PRODUCTS SPECIFICALLY DESIGNED FOR A DEMANDING AND COMPETITIVE MARKET THAT REQUIRES COMPLIANCE TO SPECIFIC STANDARDS.

100⁺

Countries where Lattuada machines are installed

90⁺

Countries where we are present

40⁺

Agents worldwide



HEADQUARTER



NORTHWOOD (OH) A PRECISE CORPORATE CHOICE TO STAY CLOSE TO OUR CUSTOMERS

LNA provides all pre- and after-sale services directly from the United States, including a qualified and highly professional technical support service with longstanding experience in the glass-working machine industry.

This new company allows us to offer endless benefits to all our US customers:

- no more problems related to transportation issues;
- machinery are invoiced directly from the United States, eliminating the currency problem;
- specific services for the US market;
- technical support always available with no more time zone issues;
- spare parts are supplied directly from LATTUADA NORTH AMERICA.

integrAL

ADDING VALUES FOR INTEGRAL SOLUTIONS

INTEGRAL IS LATTUADA'S COMBINATION
OF PRODUCTS, SERVICES AND TECHNOLOGY
TO OFFER A SINGLE, CENTRALISED MANAGEMENT
IN GLASS AND STONE PROCESSING.




SPECIAL MACHINES SOLUTIONS

Do you have any special needs?
Out-of-standard processes?
Do you treat composite materials?
That's not a problem.
We can find the most suitable
solution for you and customise
our machines to ensure you get
the flexibility you need.



STONE SOLUTIONS

Lattuada's many years of know-how transferred to
natural stone, ceramic and composite material processing:
PETRA, vertical edge polisher - Works with precision and quality
on all types of edges, and, thanks to its natural versatility, is perfect
for Stone Professionals production facilities.





GLASS SOLUTIONS

Customisation, precision, versatility: all of Lattuada glass processing lines ensure excellent performance and high productivity, integrating perfectly into company realities. A combination of experience and innovation to meet any kind of challenge.



> Grinding

Our strength, always. A variety of solutions taking the shape of a wide range of machines: more than 40 models that can be specifically configured to ensure maximum productivity.



> Washing

For more than 15 years we have been studying and providing solutions for glass washing. We offer a full range of high-tech, vertical washing machines that are easy to use and maintain.



> Complementary processing

Do you need to drill or process corners? We can provide a complete range of horizontal drilling machines and automatic radius and straight corners grinding machines.



AUTOMATION SOLUTIONS

Robotics, A-WR & i-AL Systems, Augmented Reality and IoT: a beating heart of innovation and technology revolutionising glass and stone processing. Lattuada Automation Solutions bring companies into the world of Industry 4.0, by making every machine a concentrate of precision, productivity and automation.

“ Made in Lattuada
integrated solutions,
to meet all your needs ”

ROBOTIC SOLUTIONS

LATTUADA-KNITTEL ROBOTIC SOLUTIONS +ADDED VALUES

- 01 CUSTOMISABLE SUCTION CUPS**
vacuum with Venturi system
OPTION: energy-efficient vacuum smart modules with NFC technology (*)
- 02 HIGH FLEXIBILITY**
side by side processing of glasses of different sizes with minimum distance between them
- 03 AUTOMATIC MEASUREMENT OF GLASS**
pre-setting glass size is not required
- 04 EASE OF USE**
straight-line edging machines with standard maintenance
- 05 AUTOMATIC SPEED ADJUSTMENT**
depending on the sizes of the glass
- 06 LOWER COSTS**
only one operator is required
- 07 INCREASED PRODUCTIVITY / PERFORMANCE**
thanks to the high speed of this system
- 08 FULLY AUTOMATION OF MACHINES**
reducing the need to access to the area, safety and productivity increase (possibility of remote control)
- 09 POSSIBILITY OF INTEGRATION EXPANSION / MODULARITY**
with other machines
- 10 CONTINUITÀ GARANTITA**
thanks to low maintenance required by Lattuada/Knittel machines (possibility of video monitoring and remote assistance, including via Whatsapp)
- 11 SAFETY**
plausibility check of loaded pieces.
Special sensors able to read all types of glasses
Measurement and compensation of unloading position (glasses loaded on rack without "ZERO" position)



ENERGY EFFICIENCY:

(*) OPTIONAL:

ENERGY EFFICIENT
ENERGY EFFICIENT VACUUM SMART
MODULES WITH NFC TECHNOLOGY
OPTIMIZED ROUTE AND
PATH PLANNING
TASK OPTIMIZED ROBOT SIZING
EFFICIENT CELL PLANNING
OPTIMIZED GEARBOXES AND
HIGH EFFICIENCY MOTORS

AUTOMATIC MACHINES

A-WR SYSTEM

Introduces a completely automatic wheels setting management.

01. Automatic pre-setting "ZERO" procedure of diamond and resin wheels, without glass in less than one minute
02. Automatic recover of the polishing wheels' wear, automatic tool increment based on predetermined parameters
03. Automatic positioning for the wheel's replacement
04. Jog increase/decrease of the spindle position (accuracy 0.01 mm)
05. Automatic positioning on setpoint
06. Automatic backlash recovery
07. Automatic spindle cleaning procedure
08. Wheels wear warning
09. Spindle's problems warning
10. Manual unlocking for any situation
11. Motorized adjustable inlet conveyor
12. Digital ammeters and automatic alert system for the polishing wheels wear
13. Automatic detecting and compensating procedure of the inlet conveyor belt wear
14. Inlet conveyor alignment control procedure
15. Automatic adjustment of processing parameters according to glass thickness
16. Precision resin tool absorption detection system (for remote control) and independent rotation speed adjustment

OPTIONAL: thickness control sensor or automatic thickness detection and positioning sensor



i-AL

A comprehensive pack of mechanical, electronic and software systems especially designed to deliver the maximum possible automation in glass processing and a full integration with your entire production system.

i-AL PACK INCLUDES:

01. Digital ammeters displayed on the touch-screen panel
02. Motorized glass removal setting with portable push-button panel
03. Automatic management of all processing parameters
04. Proportional valves for pressure regulation of the polishing spindles
05. Glass length measurement

OPTIONAL: thickness control sensor or automatic thickness detection and positioning sensor



GRINDING

SOLUTIONS

STRAIGHT-LINE **EDGING MACHINES**

AL M SERIES

TL SERIES

TLR SERIES

TLS SERIES

STRAIGHT-LINE **BEVELLING MACHINES**

GAMMA SERIES



THE WIDEST LINE AVAILABLE IN THE MARKET

GRINDING SOLUTIONS

- > STRAIGHT-LINE EDGING MACHINES
- > STRAIGHT-LINE BEVELLING MACHINES



As our core-business since our foundation, the Lattuada's offering includes more than 40 models of **straight-line edging machines, double-edgers** - which come in several different configurations - **and straight-line bevelling machines** suitable to meet any production need.



performing

**high loading capacity,
jumbo thicknesses**

Our machines can carry sheets weighing up to 1,500 Kg and machine thicknesses measuring up to 100 mm.



productive

smart technology

Automation is an ever-important factor: combining the need for providing high-quality products, without jeopardising flexibility while increasing productivity and cutting costs all at once.



reliable

low maintenance required

We commit towards achieving excellence by making precise choices: saying no to makeshift solutions. We have set up an internal and external supply chain that ensures the highest standards of reliability.



flexible

customised configurations

Our machines are custom-made, to give you more. Consisting of an excellent base structure, they can be configured to meet your needs.



smart

simplicity of use


Easily accessible sophisticated technology: this is our approach when it comes to building machines.



excellent

top performance

Thanks to our know-how developed and perfected in 40 years of research and activity in grinding, we - at Lattuada - design and manufacture machines that guarantee maximum processing end quality.





STRAIGHT-LINE EDGING MACHINES



TECHNICAL DETAILS

Our strength, ever.

A variety of solutions that take the form of a wide range of machines: **more than 40 models that can be specifically configured to ensure maximum productivity.**



- 1-2 **Conveyor** with support **pads**.
- 3-4 Automatic **lubrication system**.
- 5-6 **Lattuada spindles**: a unique solution for the motion transmission.
- 7-8 **Copper pipes for cooling the wheels** and the internal of the spindle tank.
- 9-10 **Electrical system** with supreme quality components, compliant with the **UL/CSA standards** too. **IE3 high efficiency motors**.
- 11 **Digital ammeters** with an automatic polishing wheels wear detection system.



AL M SERIES

RECOMMENDED EVEN FOR LARGE-SCALE PRODUCTION OF MEDIUM THICKNESS SHEETS

Having been conceived and manufactured using some of the technological solutions adopted for the larger series of edging machines, such as the assembly of the same spindles, AL M edging machines can handle high production levels.


These details contribute towards increasing their useful life, while simultaneously reducing the required maintenance.



3 - 20/25 mm
1/8 - 3/4 / 1 "



2000 mm
78.7 "



2400 - 3000 mm
94.5 - 118.1 "



400 Kg - 200 Kg/m
881 lbs - 11.2 lbs/ "




700 Kg
1,543 lbs





AL M SERIES

Electronic straight-line edging machines for processing the **flat edge with arris**



AL T SERIES

Peripheral straight-line edging machines for processing the **pencil edge, OG or flat edge with arris**



AL M SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**

AL 6 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 20 mm	12,5	5.755x1.450 xH2.400 mm	400 Kg - 200 Kg/m	700 Kg			
	us	20 - 157 "/min	H2.4 " opt. H1.4 "	1/8 - 3/4 "		226.5x57 xH94.5 "	881 lbs - 11.2 lbs/"	1,543 lbs			

AL 7 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 25 mm	15	6.285x1.450 xH3.000 mm	400 Kg -200 Kg/m	700 Kg				
	us	20 - 157 "/min	H2.4 " opt. 1.4 "	1/8 - 1 "		247.4x57 xH118.1 "	881 lbs - 11.2 lbs/"	1,543 lbs				

AL 8 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 25 mm	15	6.285x1.450 xH3.000 mm	400 Kg -200 Kg/m	700 Kg					
	us	20 - 157 "/min	H2.4 " opt. H1.4 "	1/8 - 1 "		247.4x57 xH118.1 "	881 lbs - 11.2 lbs/"	1,543 lbs					

AL 9 M	eu	0,5 - 4 m/min	H60 mm opt. H35 mm	3 - 25 mm	17	6.285x1.450 xH3.000 mm	400 Kg -200 Kg/m	700 Kg						
	us	20 - 157 "/min	H2.4 " opt. H1.4 "	1/8 - 1 "		247.4x57 xH118.1 "	881 lbs - 11.2 lbs/"	1,543 lbs						

LEGEND



speed



minimum glass
size



miter
inclination



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



max glass
load (total)



dubbing
device

ALT SERIES

Peripheral straight-line edging machines for processing the **pencil edge, OG or flat edge with arris**

										
AL 4 T	eu	0,5 - 4 m/min	H60 mm	3 - 20 mm	10	6.285x1.450 xH2.400 mm	400 Kg -200 Kg/m	700 Kg		
	us	20 - 157 "/min	H2.4 "	1/8 - 3/4 "		247.4x57 xH94.5 "	881 lbs - 11.2 lbs/"	1,543 lbs		
								4	3	2
										

AL 6 T	eu	0,5 - 4 m/min	H60 mm	3 - 20 mm	12,5	6.285x1.450 xH2.400 mm	400 Kg -200 Kg/m	700 Kg			
	us	20 - 157 "/min	H2.4 "	1/8 - 3/4 "		247.4x57 xH94.5 "	881 lbs - 11.2 lbs/"	1,543 lbs			
							6	5	4	3	2
											


diamond
peripheral
wheel


peripheral
polishing
wheel


diamond cup
wheel


resin cup
wheel


polishing cup
wheel


cerium impregnated
cup wheel


felt cup
wheel


polishing arris
wheel


diamond arris
wheel


felt arris
wheel

T SERIES

**RECOMMENDED FOR LARGE SCALE
PRODUCTION OF TEMPERED GLASS
AND/OR HIGH-QUALITY FURNISHING GLASS**


Thanks to the reinforced guides and higher pads, TL edging machines can bear greater weight as compared to the previous series. This makes them particularly flexible, given that they can process from glass sheets featuring major thicknesses to small glass strips, up to a minimum of 35 mm in height.



3 - 40 mm
1/8 / 1.5 "



2600 mm
102.4 "



3100 mm
122 "



800 Kg - 250 Kg/m
1,763 lbs - 14 lbs/ "



1,600 Kg
3,527 lbs




TL SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**



TL AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**



TL SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**

								
TL 10 PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 40 mm opt. 3 - 50 mm	20	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/'	3,527 lbs
	3* OPTIONAL 							

TL 10 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 40 mm opt. 3 - 50 mm	21	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/''	3,527 lbs
	3* OPTIONAL  10  9  8  7  6  5  4  3*  2  1 							

TL 11 PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 40 mm opt. 3 - 50 mm	22	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/''	3,527 lbs
	11 10 9 8 7 6 5 4 3 2 1							



LEGEND



speed



minimum glass
size



miter
inclination



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



max glass
load (total)




dubbing
device

TL AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**

TL 9 AV PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 40 mm opt. 3 - 50 mm	21	7.920x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 1.5 " opt. 1/8 - 2 "		311x62.2 xH122.8 "	1,763 lbs - 14 lbs/'	3,527 lbs
	987654321								

TL 10 AV PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 40 mm opt. 3 - 50 mm	23	8.210x1.600 xH3.120 mm	800 Kg - 250 Kg/m	1.600 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 1.5 " opt. 1/8 - 2 "		332.2x62.2 xH122 "	1,763 lbs - 14 lbs/'	3,527 lbs
	3* OPTIONAL  19  9  8  7  6  5  4  3*  2  1 								



TIR SERIES

THE MOST WIDELY USED BY
MAJOR GROUPS OF NORTHERN
EUROPE AND USA

Designed for glassmakers handling major volumes
of large sheets and high thicknesses for heavy duty
construction, or for supreme quality works at high speed.



3 - 50 / 55 mm
1/8 - 2 / 2.2 "



2.600 mm / 3.000 mm
102.3 / 118.1 "




3.100 mm / 3.700 mm
122 / 145.6 "



1.100 Kg - 350 Kg/m
2,425 lbs - 19.6 lbs/ "



2.000 Kg
4,409 lbs




TLR SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**



TLR AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**



TLR SERIES

Electronic straight-line edging machines
for processing the **flat edge with arris**

								
TLR 11 PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 50 mm	22	8.210x1.1600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2 "		323.2x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	3* OPTIONAL 		11  10  9  8  7  6  5  4  3*  2  1 					

TLR 11 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 50 mm	22	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2 "		335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	3* OPTIONAL 		11  10  9  8  7  6  5  4  3*  2  1 					

TLR 11 DD PC	eu	0,3 - 5 m/min*	H60 mm	3 - 50 mm**	22	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H2.4 "	1/8 - 2 ***		335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	3*  OPTIONAL		* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)		           			

TLR12C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 50 mm	23	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2 "		335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	12 11 10 9 8 7 6 5 4 3 2 1							

TLR 12 DD PC	eu	0,3 - 5 m/min*	H60 mm	3 - 50 mm**	22	8.970x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H2.4 "	1/8 - 2 ***		353.1x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
			* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)		            			

LEGEND



speed



minimum glass
size



miter
inclination



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



max glass
load (total)



dubbing
device

Electronic straight-line edging machines for processing the **flat edge with arris**



TLR 14 C PC	eu	0,3 - 5 m/min	H60 mm opt. H35 mm	3 - 55 mm	30	9.590x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H2.4 " opt. 1.4 "	1/8 - 2.2 "		377.5x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	14 13 12 11 10 9 8 7 6 5 4 3 2 1							



felt arris
wheel

TLR AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**






TLR 10 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 50 mm	23	8.510x1.600 xH3.100 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "				335x62.2 xH122 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
TLR 11 AV PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 50 mm	23	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "				335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
TLR 11 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45° opt. 0 - 60°	3 - 50 mm	23	8.510x1.600 xH3.120 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "				335x62.2 xH122.8 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
TLR 11 AV C DD PC	eu	0,3 - 5 m/min*	H85 mm	0 - 45°	3-50 mm**	25	8.970x1.600 xH3.100 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H3.3 "		1/8 - 2 ***		353.1x62.2 xH122 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
			* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device)						

LEGEND

								
speed	minimum glass size	miter inclination	workable glass thickness	installed power	dimensions	max glass load (on the conveyor)	max glass load (total)	dubbing device

TLR AV SERIES

Electronic straight-line edging machine
with **variable angle between 0 and 45°**

									
TLR 13 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45°	3-55 mm	28	9.590x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 2.2 "		377.6x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	13121110987654321 								
TLR 13 AV C DD PC	eu	0,3 - 5 m/min*	H85 mm opt. H60 mm	0 - 45°	3 - 55 mm**	30	10.020x1.600 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min*	H3.3 " opt. H2.4 "		1/8 - 2.2 ***		394.5x62.2 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	* max 3,5 m/min (max 137 "/min) (with dubbing device) ** max 15 mm (max 0.6 ") (with dubbing device) 1413121110987654321 								
TLR 14 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45°	3 - 55 mm	30	10.040x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 2.2 "		377.6x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	1413121110987654321 								
TLR 16 AV C PC	eu	0,3 - 5 m/min	H85 mm opt. H60 mm	0 - 45°	3 - 55 mm	34	10.390x1.700 xH3.700 mm	1.100 Kg - 350 Kg/m	2.000 Kg
	us	12 - 197 "/min	H3.3 " opt. H2.4 "		1/8 - 2.2 "		409x66.9 xH145.6 "	2,425 lbs - 19.6 lbs/"	4,409 lbs
	16151413121110987654321 								



TLS SERIES

THE EVOLUTION OF OUR FAMILY OF TLR EDGING MACHINES

Thanks to some structural changes, mainly due to the application of new pads and reinforced guides, the models of this series are capable of carrying sheets weighing up to 1,500 Kg (on the conveyor) and processing sheets with thickness up to 100 mm.



3 - 60 / 80 / 100 mm
1/8 - 2.4 / 3.1 / 3.9 "



3.000 mm
118.1 "





3.700 mm
145.6 "



1.100 Kg - 350 Kg/m
2,425 lbs - 19.6 lbs/ "



2.200 Kg
4,850 lbs



TLS AV SERIES


Electronic straight-line edging machine
with **variable angle between 0 and 45°**





**THE BIGGEST
EDGING MACHINE
EVER BUILT!**

										
TLS 15 AV C PC	sp60/80/100	eu	0,3 - 5 m/min	H85 mm	0 - 45°	3 - 60/80/100 mm	32	10.390x1.750 xH3.700 mm	1.100 Kg - 350 Kg/m opt. 1.500 Kg - 350 Kg/m	2.200 Kg
		us	12 - 197 "/min	H3.3 "		1/8 - 2.4/3.1/3.9 "		409x68.9 xH145.6 "	2,425 lbs - 19.6 lbs/" opt. 3,307 lbs - 19.6 lbs/"	4,850 lbs
		15 14 13 12 11 10 9 8 7 6 5 4 3 2 1								





ACCESSORIES

STRAIGHT-LINE EDGING MACHINES

The washing machine applied to the edging machines and bevelling machines outlet conveyor allows the complete cleaning and drying of the processed edges of the glass sheets.



OT 300	eu	300x300 mm	the same of the machine on which it is fitted on	2 *	550x600 xH770 mm	2
	us	11.8x11.8 "			21.6x23.6 xH30.3 "	
				*standard (t may change according to the included options)		

PAR-AL: device for processing parallelogram-shaped glasses.



LOOK AT THE DEVICE AT WORK





PANEL

TOUCH SCREEN OPERATOR

The **only one in the market** capable of guaranteeing constant monitoring of the various functions of the machine through different control methods.

BASIC 4 "

Machine's data and maintenance information panel



ADVANCED 10 "

Panel for the control and management of all work steps



ADVANCED 12 "

Panel for the control and management of all work steps for automatic machines (with A-WR and i-AL packages)




STRAIGHT-LINE BEVELLING MACHINES

TECHNICAL DETAILS

Bevelling has always considered the **most complex edging operation**.

This is why Lattuada manufactures very precise and accurate bevelling machines, renowned for their reliability, low maintenance and duration over time.



- 1 **Numerous wheel configurations** available, even customised.
- 2 **Quick and simple** wheel change.
- 3 Managing all work steps through a **touch screen operator panel**.
- 4 **Small piece processing** system.
- 5 OT 300 **washing machine**.
- 6 Motor absorption **digital ammeters**.
- 7 Pads washing **rotary brush**.
- 8 **Automatic** lubrication.
- 9 Variation of the conveyor speed by **means of the inverter**.
- 10 Version with 4 felts: **high processing speed and quality!**



GAMMA

SERIES

THE WIDEST RANGE CURRENTLY AVAILABLE IN THE MARKET, IT OFFERS TECHNICAL SOLUTIONS CAPABLE OF MEETING ANY PRODUCTION NEED

GAMMA 8, which combines the versatility of a small machine with the capacity of processing on sizeable productions, even thanks to the three felts it is provided with, we go all the way to the “elder sisters”: recommended for glassmakers in need of machines capable of operating at high speeds and with utmost quality level.



3 - 20 / 25 mm
1/8 - 3/4 / 1"



2.000 / 2.600 mm
78.7 / 102.3"





2.450 / 3.100 mm
96.5 / 122"



500 Kg - 150 Kg/m
1,102 lbs - 8.4 lbs/"




mechanical



GAMMA SERIES

Straight-line bevelling machines
for processing **the bevel** and **flat edge with arris**,
using **liquid cerium oxide**



GAMMA SERIES

Straight-line bevelling machines for processing
the **polished bevel** using **liquid cerium oxide**

				STANDARD	OPTIONAL							
GAMMA 8 PC	eu	0,5 - 4 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	40 mm	3 - 20 mm	18	6.510x1.350 xH2.450 mm	500 Kg - 150 Kg/m		
	us	20 - 157 "/min	4.3x4.3 " opt. 1.6x1.6 "			1.6 "	1/8 - 3/4 "		256.2x53.1 xH96.5 "	1,102 lbs - 8.4 lbs/m		
		3* OPTIONAL									8 7 6 5 4 3* 2 1	
GAMMA 613 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	23	8.420x1.600 xH3.100 mm	500 Kg - 150 Kg/m		
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		331.4x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m		
		4* OPTIONAL									10 9 8 7 6 5 4* 3 2 1	
GAMMA 614 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	26	8.420x1.600 xH3.100 mm	500 Kg - 150 Kg/m		
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		331.4x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m		
		4* OPTIONAL									11 10 9 8 7 6 5 4* 3 2 1	
GAMMA 713 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	26	8.420x1.600 xH3.100 mm	500 Kg - 150 Kg/m		
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		331.4x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m		
		4* OPTIONAL									11 10 9 8 7 6 5 4* 3 2 1	

Straight-line bevelling machines for processing
the **bevel and pencil edge**, using **liquid cerium oxide**

GAMMA 633 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	3 - 25°	50 mm	3 - 25 mm	27	8.880x1.600 xH3.100 mm	500 Kg - 150 Kg/m		
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "			2 "	1/8 - 1 "		349.6x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m		
		7* OPTIONAL									12 11 10 9 8 7* 6 5 4 3 2 1	

Straight-line bevelling machines for processing
the **bevel and flat edge with arris**, using **liquid cerium oxide**

GAMMA 643 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	50 mm	3 - 25 mm	32	8.880x1.600 xH3.100 mm	500 Kg - 150 Kg/m			
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "		2 "	1/8 - 1 "		349.6x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m			
											13 12 11 10 9 8 7 6 5 4 3 2 1	
GAMMA 723 PC	eu	0,3 - 5 m/min	110x110 mm opt. 40x40 mm	3 - 45°	50 mm	3 - 25 mm	32	8.880x1.600 xH3.100 mm	500 Kg - 150 Kg/m			
	us	12 - 197 "/min	4.3x4.3 " opt. 1.6x1.6 "		2 "	1/8 - 1 "		349.6x62.2 xH123.2 "	1,102 lbs - 8.4 lbs/m			
		OPTIONAL 4* 12*									12* 11 10 9 8 7 6 5 4* 3 2 1	



ACCESSORIES

STRAIGHT-LINE BEVELLING MACHINES

The washing machine applied to the edging machines and beveling machines outlet conveyor allows the complete cleaning and drying of the processed edges of the glass sheets.



OT 300	eu	300x300 mm	the same of the machine on which it is fitted on	Kw. 2 *	550x600xH770 mm	2
	us	11.8x11.8 "			21.6x23.6xH30.3 "	

*standard (it may change according to the included options)


PANEL

TOUCH SCREEN OPERATOR

The **only one in the market** capable of guaranteeing constant monitoring of the various functions of the machine through different control methods.

ADVANCED 10.4 "

Panel for the control and management of all work steps



diamond cup wheel



peripheral polishing wheel



diamond cup wheel



resin cup wheel



polishing cup wheel



felt cup wheel



polishing aris wheel



WASHING

SOLUTIONS

VERTICAL WASHING MACHINES

OT SERIES

CT SERIES

CTS SERIES

WASHING AND DRYING GLASS SHEETS

WASHING SOLUTIONS

Lattuada washing machines can be integrated with different machines, such as vertical grinding, drilling and milling lines as well as CNC machines.

They differ in terms of the useful washing height, number of brushes and total loadable weights. The machine body and all parts exposed to contact with water are made of stainless steel or stainless material.



performing

high washing and drying capacity

Lattuada design criteria increasingly focused on each and every need as well as construction and structural robustness offer high washing and drying quality washing machines, even at high speeds and on any type of glass.



productive

smart technology

Suitable for high production loads, our washing machines can run 24/7 non-stop.



reliable

little maintenance required

All points requiring maintenance are easily accessible and the maintenance operations to be carried out are simple and quick to perform.



flexible

customised configurations

All Lattuada washing machine models are highly customisable and can be integrated with different machines, such as vertical grinding, drilling and milling lines as well as CNC machines.



smart

simplicity of use


Easily accessible sophisticated technology; this is our approach when it comes to building machines.



excellent

top performance




Thanks to our know-how developed and perfected in 40 years, we - at Lattuada - design and manufacture machines that offer utmost washing and drying final quality.





VERTICAL WASHING MACHINES

TECHNICAL DETAILS

Attention to details generates supreme quality products.
Highly reliable state-of-the-art machines, in terms of precision,
are our company's strong points.



- 1 **Rollers for glass sheets** transport (special version for heavy loads).
- 2 Conveyors with belts **for washing shaped glasses**.
- 3 Brushes available for **Low-E glass** too.
- 4 Glass **anti-chute sensor and pedal**.
- 5 **Brush motors** positioned at the top part of the washing machine.
- 6 Option to **position in line** with our edging and bevelling machines.
- 7 Soundproofed **high-pressure fan**.
- 8 **Components certified** in compliance with the UL-CSA standards.
- 9 **Hot water** for pre-washing, first washing or rinsing section.
- 10 Black panel with **inspection lights**.
- 11 High **soundproof** level.



OT SERIES

OPEN TOP VERTICAL WASHING MACHINES

When stored, glasses are usually exposed to the risk of being scratched due to the dirt that deposits on them during processing.

This problem can be solved by using an OT series washing machine, designed for washing and drying sheets, and which can be integrated with different machines, such as vertical grinding, drilling and milling lines as well as CNC machines.



3 - 15 / 20 / 25 mm
1/8 - 0.6 / 3/4 / 1 "




350xH100 mm
13.8xH3.9 "



200 / 300 / 500 kg
441 / 661 / 1,102 lbs



2 / 4 / 6



OT 1600 | OT 2000 SERIES

Open top vertical
washing machines



OT 1600 SERIES

Open top vertical washing machines

  min  max   Kw.   max 									
OT 1600/200/2s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 15 mm opt. 3 - 19 mm	7**	5.970x2.000 xH2.520 mm	200 Kg	2
	us	19.7 - 197 "/min	13.8xH3.9 "**	63 "	1/8 - 0.6 " opt. 1/8 - 0.7 "		235x78.7 xH99.2 "	441 lbs	
OT 1600/200/4s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 15 mm opt. 3 - 19 mm	7**	6.240x2.000 xH2.520 mm	200 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 "**	63 "	1/8 - 0.6 " opt. 1/8 - 0.7 "		245.6x78.7 xH99.2 "	441 lbs	
OT 1600/300/4s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 20 mm opt. 3 - 30 mm	9**	6.240x2.000 xH2.520 mm	300 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 "**	63 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		245.6x78.7 xH99.2 "	661 lbs	
OT 1600/300/6s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 20 mm opt. 3 - 30 mm	9**	6.720x2.000 xH2.520 mm	300 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 "**	63 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		264.5x78.7 xH99.2 "	661 lbs	
OT 1600/500/4s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 25 mm opt. 3 - 40 mm	9**	6.710x2.000 xH2.520 mm	500 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 "**	63 "	1/8 - 1 " opt. 1/8 - 1.6 "		264.1x78.7 xH99.2 "	1,102 lbs	
OT 1600/500/6s	eu	0,5 - 5 m/min	350xH100 mm*	1.600 mm	3 - 25 mm opt. 3 - 40 mm	9**	7.210x2.200 xH2.520 mm	500 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 "**	63 "	1/8 - 1 " opt. 1/8 - 1.6 "		283.8x86.6 xH99.2 "	1,102 lbs	

LEGEND



speed



minimum
glass size



maximum
glass size



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



brushes

OT 2000 SERIES

Open top vertical washing machines



OT 2000/300/4S	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 20 mm opt. 3 - 30 mm	g**	6.240x2.000 xH2.920 mm	300 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 "**	78.7 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		245.6x78.7 xH114.9 "	661 lbs	
OT 2000/300/6S	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 20 mm opt. 3 - 30 mm	g**	6.720x2.000 xH2.920 mm	300 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 "**	78.7 "	1/8 - 3/4 " opt. 1/8 - 1.2 "		264.5x78.7 xH114.9 "	661 lbs	
OT 2000/500/4S	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 25 mm opt. 3 - 40 mm	14**	6.720x2.000 xH2.920 mm	500 Kg	4
	us	19.7 - 197 "/min	13.8xH3.9 "**	78.7 "	1/8 - 1 " opt. 1/8 - 1.6 "		264.5x78.7 xH114.9 "	1,102 lbs	
OT 2000/500/6S	eu	0,5 - 5 m/min	350xH100 mm*	2.000 mm	3 - 25 mm opt. 3 - 40 mm	14**	7.210x2.200 xH2.920 mm	500 Kg	6
	us	19.7 - 197 "/min	13.8xH3.9 "**	78.7 "	1/8 - 1 " opt. 1/8 - 1.6 "		283.8x86.6 xH114.9 "	1,102 lbs	

* others on request
** standard (may vary depending on options potentially included)

CT SERIES

VERTICAL WASHING MACHINES CLOSED ON TOP

When stored, glasses are usually exposed to the risk of being scratched due to the dirt that deposits on them during processing. This problem can be solved by using a CT series washing machine, designed for washing and drying sheets, and which can be integrated with different machines, such as vertical grinding, drilling and milling lines as well as CNC machines.



3 - 25 mm
1/8 - 1 "




400xH100
15.7x3.9 "



500 kg
1,102 lbs




4 / 6



CT 2600 | CT 3300 SERIES

Vertical washing machines
closed on top



CT 2600 SERIES

Vertical washing machines closed on top



CT 2600/500/4s	eu	0,5 - 5 m/min	400xH100 mm*	2.600 mm	3 - 25 mm opt. 3 - 40 mm	19**	7.950x2.570 xH3.590 mm	500 Kg opt. 800 Kg	4
	us	19.7 - 197 "/min	15.7xH3.9 "**	102.3 "	1/8 - 1 " opt. 1/8 - 1.6 "		321.9x101.1 xH141.3 "	1,102 lbs opt. 1,764 lbs	

CT 2600/500/6s	eu	0,5 - 5 m/min	400xH100 mm*	2.600 mm	3 - 25 mm opt. 3 - 40 mm	23**	8.670x2.570 xH3.590 mm	500 Kg opt. 800 Kg	6
	us	19.7 - 197 "/min	15.7xH3.9 "**	102.3 "	1/8 - 1 " opt. 1/8 - 1.6 "		341.3x101.1 xH141.3 "	1,102 lbs opt. 1,764 lbs	



speed



minimum
glass size



maximum
glass size



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)



brushes

SERIE CT 3300

Vertical washing machines closed on top



CT 3300/500/4S	eu	0,5 - 5 m/min	400xH100 mm*	3.300 mm	3 - 25 mm opt. 3 - 40 mm	23**	9.440x2.570 xH4.290 mm	500 Kg opt. 800 Kg	4
	us	19.7 - 197 "/min	15.7xH3.9 "**	129.9 "	1/8 - 1 " opt. 1/8 - 1.6 "		371.6x101.1 xH168.8 "	1,102 lbs opt. 1,764 lbs	

CT 3300/500/6S	eu	0,5 - 5 m/min	400xH100 mm*	3.300 mm	3 - 25 mm opt. 3 - 40 mm	23**	10.160x2.570 xH4.290 mm	500 Kg opt. 800 Kg	6
	us	19.7 - 197 "/min	15.7xH3.9 "**	129.9 "	1/8 - 1 " opt. 1/8 - 1.6 "		400x101.1 xH168.8 "	1,102 lbs opt. 1,764 lbs	

* others on request
** standard (may vary depending on options potentially included)

CTS SERIES

VERTICAL WASHING MACHINES CLOSED ON TOP

The Lattuada CTS series models are washing machines designed for glassmakers handling **major volumes of large sheets and high thicknesses.**



3 - 60/80 mm
1/8 - 2.3/3.1 "





400xH100
15.7x3.9 "



800/1,500 kg
1,764/3,306 lbs



4/6




CTS 2600 | CTS 3300 SERIES

Vertical washing machines
closed on top



CTS 2600 SERIES

Vertical washing machines **closed on top**

									
CTS 2600 800/4s	eu	0,5 - 5 m/min	400xH100 mm*	2.600 mm	3 - 60 mm	23**	7.950x2.570 xH3.590 mm	800 Kg opt. 1.000 Kg	4
	us	19.7 - 197 "/min	15.7xH3.9 "**	102.3 "	1/8 - 2.3 "		321.9x101.1 xH141.3 "	1,764 lbs opt. 2,204 lbs	
CTS 2600 800/6s	eu	0,5 - 5 m/min	400xH100 mm*	2.600 mm	3 - 60 mm	23**	8.670x2.570 xH3.590 mm	800 Kg opt. 1.000 Kg	6
	us	19.7 - 197 "/min	15.7xH3.9 "**	102.3 "	1/8 - 2.3 "		341.3x101.1 xH141.3 "	1,764 lbs opt. 2,204 lbs	
CTS 2600 1500/4s	eu	0,5 - 5 m/min	400xH100 mm*	2.600 mm	3 - 80 mm	23**	8.780x2.585 xH3.590 mm	1.500 Kg opt. 2.000 Kg	4
	us	19.7 - 197 "/min	15.7xH3.9 "**	102.3 "	1/8 - 3.1 "		345.6x101.7 xH141.3 "	3,306 lbs opt. 4,409 lbs	
CTS 2600 1500/6s	eu	0,5 - 5 m/min	400xH100 mm*	2.600 mm	3 - 80 mm	23**	9.120x3.590 xH3.590 mm	1.500 Kg opt. 2.000 Kg	6
	us	19.7 - 197 "/min	15.7xH3.9 "**	102.3 "	1/8 - 3.1 "		359x101.7 xH141.3 "	3,306 lbs opt. 4,409 lbs	

CTS 3300 SERIES

Vertical washing machines **closed on top**

									
CTS 3300 800/4s	eu	0,5 - 5 m/min	400xH100 mm*	3.300 mm	3 - 60 mm	23**	9.440x2.570 xH4.290 mm	800 Kg opt. 1.000 Kg	4
	us	19.7 - 197 "/min	15.7xH3.9 "**	129.9 "	1/8 - 2.3 "		371.6x101.1 xH168.8 "	1,764 lbs opt. 2,204 lbs	
CTS 3300 800/6s	eu	0,5 - 5 m/min	400xH100 mm*	3.300 mm	3 - 60 mm	23**	10.160x2.570 xH4.290 mm	800 Kg opt. 1.000 Kg	6
	us	19.7 - 197 "/min	15.7xH3.9 "**	129.9 "	1/8 - 2.3 "		400x101.1 xH168.8 "	1,764 lbs opt. 2,204 lbs	
CTS 3300 1500/4s	eu	0,5 - 5 m/min	400xH100 mm*	3.300 mm	3 - 80 mm	23**	10.270x2.585 xH4.290 mm	1.500 Kg opt. 2.000 Kg	4
	us	19.7 - 197 "/min	15.7xH3.9 "**	129.9 "	1/8 - 3.1 "		404.3x101.7 xH168.8 "	3,306 lbs opt. 4,409 lbs	
CTS 3300 1500/6s	eu	0,5 - 5 m/min	400xH100 mm*	3.300 mm	3 - 80 mm	23**	10.610x2.585 xH4.290 mm	1.500 Kg opt. 2.000 Kg	6
	us	19.7 - 197 "/min	15.7xH3.9 "**	129.9 "	1/8 - 3.1 "		417.7x101.7 xH168.8 "	3,306 lbs opt. 4,409 lbs	

* others on request ** standard (may vary depending on options potentially included)

LEGEND



speed



minimum
glass size



minimum
glass size



workable glass
thickness



installed
power



dimensions



max glass load
(on the conveyor)




brushes

ACCESSORIES

VERTICAL WASHING MACHINES

The washing machine applied to **the edging machines and bevelling machines** outlet conveyor allows the complete cleaning and drying of the processed edges of the glass sheets.





OT 300	eu	300x300 mm*	the same of the machine on which it is fitted on	2 **	550x600 xH770 mm	2
	us	11.8x11.8 **			21.6x23.6 xH30.3 "	
				* others on request ** standard (may vary depending on options potentially included)		

PANEL

TOUCH SCREEN OPERATOR

Panel for the control and management of all work steps



The background is a dark charcoal grey. On the left side, there is a large, stylized purple shape that resembles a mountain range or a series of overlapping triangles. Below this, there is a horizontal purple bar with rounded ends. At the bottom of the page, there is another horizontal purple bar, also with rounded ends, extending from the left edge towards the right.

COMPLEMENTARY

PROCESSING SOLUTIONS

CORNERS GRINDING MACHINES

DELTA SERIES

HORIZONTAL **DRILLING** MACHINES

TP SERIES

CORNERS GRINDING MACHINES AND DRILLING MACHINES

SOLUTIONS FOR COMPLEMENTARY PROCESSING

Specific machines for automatically processing radius and straight corners, thus recommended for example for glassmakers who manufacture large volumes of furnishing shelves or doors.

Complete line of automatic, semi-automatic and manual horizontal drilling machines with one or two opposing heads.



performing high speed

Corners grinding machines: cycle time less than 30" for thicknesses up to 20 mm.



productive smart technology

Drilling machines: laser centring system and supports for drilling in series.



reliable little maintenance required

Machines with extremely long useful life and extremely easy to maintain.



flexible customised configurations

Corners grinding machines: you can work on different types of corners and profiles depending on the assembled type of tools.



smart simplicity of use

Drilling machines: automatic adjustment of the diamond tool speed by setting the drilling diameter.



excellent top performance

Thanks to optionals such as the use of liquid cerium oxide, our corners grinding machines can offer high final processing quality.



CORNERS GRINDING MACHINES

TECHNICAL DETAILS

- 1 Movement of the **pneumatic wheel-holder units**.
- 2 Spindle **adjustment handwheels**.
- 3 Option to work in **automatic cycle**.
- 4 **Manual lubrication** of all rotary parts.
- 5 Integrated support for processing **medium size sheets**.
- 6 Simple and quick **positioning of the templates**.



HORIZONTAL DRILLING MACHINES

TECHNICAL DETAILS

- 1 **Automatic ejection** of the glass cores (not available for the TP 1000 version).
- 2 Laser **centring system**.
- 3 Pneumatic glass **support table**.
- 4 **Automatic adjustment of the diamond tool speed** by setting the drilling diameter (not available for the TP 1000 version).



DELTA SERIES

SPECIFIC MACHINES FOR AUTOMATIC PROCESSING OF CORNERS

The DELTA series comprises specific machines for automatically processing corners, thus recommended for example for glassmakers who manufacture large volumes of furnishing shelves or doors.

They can process radius or straight corners on thicknesses up to 20 mm in less than 30 seconds, even with liquid cerium oxide polishing.



4 - 20 mm
5/32 - 3/4 "




10 - 150 mm
25/64 - 6 "



10 - 200 mm
25/64 - 7.9 "





pneumatic




DELTA SERIES

Corners grinding machines





DELTA SERIES


Automatic machines for **processing radius and straight corners**



DELTA M3	eu	200x300 mm opt. 100x200 mm	1.000x1.000 mm (square glasses) 1.300x700 mm (rectangular glasses)	10 - 150 mm	10 - 200 mm	4 - 20 mm	8,5	2.200x1.150 xH1.750 mm
	us	7.9x11.8 " opt. 3.9x7.9 "	39.4x39.4 " (square glasses) 51.2x27.5 " (rectangular glasses)	25/64 - 6 "	25/64 - 7.9 "	25/64 - 7.9 "		86.6x45.3 xH68.9 "

DELTA M4	eu	200x300 mm opt. 100x200 mm	1.000x1.000 mm (square glasses) 1.300x700 mm (rectangular glasses)	10 - 150 mm	10 - 200 mm	4 - 20 mm	11	2.680x1.300 xH1.750 mm
	us	7.9x11.8 " opt. 3.9x7.9 "	39.4x39.4 " (square glasses) 51.2x27.5 " (rectangular glasses)	25/64 - 6 "	25/64 - 7.9 "	25/64 - 7.9 "		105.5x51.2 xH68.9 "
								4 3 2 1





DELTA M4 C	eu	200x300 mm opt. 100x200 mm	1.000x1.000 mm (square glasses) 1.300x700 mm (rectangular glasses)	10 - 150 mm	10 - 200 mm	4 - 20 mm	11	2.680x1.300 xH1.750 mm		
	us	7.9x11.8 " opt. 3.9x7.9 "	39.4x39.4 " (square glasses) 51.2x27.5 " (rectangular glasses)	25/64 - 6 "	25/64 - 7.9 "	25/64 - 7.9 "		105.5x51.2 xH68.9 "		
								4	3	2

DELTA M5	eu	200x300 mm opt. 100x200 mm	1.000x1.000 mm (square glasses) 1.300x700 mm (rectangular glasses)	10 - 150 mm	10 - 200 mm	4 - 20 mm	13	3.000x1.300 xH1.750 mm
	us	7.9x11.8 " opt. 3.9x7.9 "	39.4x39.4 " (square glasses) 51.2x27.5 " (rectangular glasses)	25/64 - 6 "	25/64 - 7.9 "	25/64 - 7.9 "		118.1x51.2 xH68.9 "
	5 4 3 2 1 							

TIP SERIES

SEMI-AUTOMATIC AND AUTOMATIC MANUAL HORIZONTAL DRILLING MACHINES

Complete line of automatic, semi-automatic and manual horizontal drilling machines with one or two opposing heads (bottom automatic and top manual). Common features are the automatic locking of the glass during the drilling cycle and the option to adjust the drilling depth on the bottom head. Just like for all of our models, they come in various options, thus allowing utmost customisation and adaptation of the product to the various needs.




Ø 4 - 200 / 250 mm
Ø 5/32 - 7.9 / 9.8 "

Ø 4 - 130 mm
Ø 5/32 - 5.1 "

50 mm
2 "

1,000 / 1,065 / 1,200 / 1,665 mm
39.3 / 41.9 / 47.2 / 65.5 "



TP SERIES

Manual and **semi-automatic**
horizontal drilling machines




TP SERIES

Manual horizontal drilling machines

							
TP 1000.1H	eu	Ø 4 - 200 mm	-	1000 mm	50 mm	1,5	1.700x1.300 xH1.800 mm
	us	Ø 5/32 - 7.9 "	-	39.4 "	2 "		66.9x51.1 xH70.8 "
TP 1000.2H	eu	Ø 4 - 200 mm	Ø 4 - 130 mm	1000 mm	50 mm	2,5	1.700x1.300 xH1.800 mm
	us	Ø 5/32 - 7.9 "	Ø 5/32 - 5.1 "	39.4 "	2 "		66.9x51.1 xH70.8 "
						Available also the automatic version	

TP SERIES

Semi-automatic/automatic horizontal drilling machines

							
TP 1065	eu	Ø 4 - 250 mm	Ø 4 - 130 mm	1.065 mm	50 mm	3	1.700x900 xH1.760 mm
	us	Ø 5/32 - 9.8 "	Ø 5/32 - 5.1 "	41.9 "	2 "		66.9x35.4 xH69.2 "
						Available also the automatic version	
TP 1200	eu	Ø 4 - 250 mm	Ø 4 - 130 mm	1.200 mm	50 mm	3	1.900x900 xH1.760 mm
	us	Ø 5/32 - 9.8 "	Ø 5/32 - 5.1 "	47.2 "	2 "		74.8x35.4 xH69.2 "
						Available also the automatic version	
TP 1200 VSE	eu	Ø 4 - 250 mm	Ø 4 - 130 mm	1.200 mm	50 mm	3	4.920x2.483 xH1.760 mm
	us	Ø 5/32 - 9.8 "	Ø 5/32 - 5.1 "	47.2 "	2 "		193.7x97.7 xH69.2 "
						Available also the automatic version	
TP 1665	eu	Ø 4 - 250 mm	Ø 4 - 130 mm	1.665 mm	50 mm	3	2.700x900 xH1.760 mm
	us	Ø 5/32 - 9.8 "	Ø 5/32 - 5.1 "	65.5 "	2 "		106.2x35.4 xH69.2 "
						Available also the automatic version	

LEGEND


drilling diameter
(with 1 head)


drilling diameter
(with 2 heads)


useful depth


max glass
thickness


installed
power


dimensions

adeliolattuada.com



ADELIO LATTUADA S.R.L.
Via Abbondanza, 11/13 - 22070 Carbonate (CO) IT
T. +39 0331.832713 - info@adeliolattuada.com
adeliolattuada.com

LATTUADA NORTH AMERICA, INC.
6967 Wales Road, Suite F - Northwood 43619 (OH)
T. +1 567 249 4486 - info@lattuada-na.com
lattuada-na.com